# 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

### 1.1 Product identifier

### Product name ENDUROSHIELD RAIN REPELLENT (EU) REACH

Synonym(s) ENDUROSHIELD RAIN REPELLENT

### 1.2 Uses and uses advised against

Use(s) PROTECTIVE COATING FOR AUTO GLASS SURFACES

### 1.3 Details of the supplier of the product

Supplier name	ENDUROSHIELD EUROPE
Address	Kuiperbergweg 29, Amsterdam Zuidoost, AE 1101, NETHERLANDS
Telephone	+ 33 670 50 48 97
Email	saleseurope@enduroshield.com
Website	http://www.enduroshield.com/

### 1.4 Emergency telephone number(s)

**Emergency** + 33 670 50 48 97

# 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

CLASSIFICATION ACCORDING TO REGULATION (EC) NO. 1272/2008 [CLP/GHS]

**GHS classification(s)** Flammable Liquids: Category 2 Specific Target Organ Systemic Toxicity (Single Exposure): Category 3 Serious Eye Damage / Eye Irritation: Category 2A

### 2.2 Label elements

LABELLING ACCORDING TO REGULATION (EC) NO. 1272/2008 [CLP/GHS]

# Signal word

DANGER

Pictogram(s)

### Hazard statement(s)

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

### Prevention statement(s)

P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.



### PRODUCT NAME ENDUROSHIELD RAIN REPELLENT

Response statement(s	
P303 + P361 + P353 P304 + P340	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P337 + P313 P370 + P378	If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media for extinction.
	in case of fire. Ose appropriate media for extinction.
Storage statement(s)	
P403 + P233 + P235 P405	Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Disposal statement(s)	
P501	Dispose of contents/container in accordance with relevant regulations.
2.3 Other hazards No information provided	

# 3. COMPOSITION/ INFORMATION ON INGREDIENTS

### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
ISOPROPYL ALCOHOL	67-63-0	200-661-7	>85 to 95%
PROPRIETARY INGREDIENT(S)	-	-	<10%

# 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

Еуе	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poison Information Centre or a doctor (at once). If swallowed, do not induce vomiting.
First aid facilities	No information provided.

### 4.2 Most important symptoms and effects, both acute and delayed

Irritating to the eyes. Vapours may cause drowsiness and dizziness.

#### 4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

### 5. FIRE FIGHTING MEASURES

### 5.1 Extinguishing media

Dry agent, carbon dioxide, foam or water fog. Prevent contamination of drains and waterways.

### 5.2 Special hazards arising from the substance or mixture

Highly flammable. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Vapour may form explosive mixtures with air. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, mobile phones, etc when handling. Earth containers when dispensing fluids.

### 5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

# ChemAlert.

# 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

### 6.2 Environmental precautions

Prevent product from entering drains and waterways.

#### 6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

# 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Large storage areas should be bunded and have appropriate ventilation systems.

### 7.3 Specific end use(s)

No information provided.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

### Exposure standards

Ingredient	Reference	TWA		STEL	
Ingredient	Kelefelice		mg/m³	ppm	mg/m³
2-Propanol	OEL (Norway)	100	245		
Propan-2-ol	OEL (Germany)	200	500		
Propan-2-ol	WEL (UK)	400	999	500	1250

### **Biological limits**

Ingredient	Determinant	Sampling Time	BEI
ISOPROPYL ALCOHOL	Acetone in urine	End of shift at end of workweek	40 mg/L

Reference: ACGIH Biological Exposure Indices

### 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.



### PRODUCT NAME ENDUROSHIELD RAIN REPELLENT

### PPE

Eye / Face	Wear splash-proof goggles.
Hands	Wear nitrile or neoprene gloves.
Body	When using large quantities or where heavy contamination is likely, wear coveralls.
Respiratory	Where an inhalation risk exists, wear a Type A (Organic vapour) respirator. If spraying, wear a Type A-Class P1 (Organic gases/vapours and Particulate) respirator.



# 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

internation on busic physical a	na chemical properties
Appearance	CLEAR TO LIGHT YELLOW LIQUID
Odour	ALCOHOL ODOUR
Flammability	HIGHLY FLAMMABLE
Flash point	12°C (cc) (Isopropanol)
Boiling point	82.4°C (Isopropanol)
Melting point	-90°C (Isopropanol)
Evaporation rate	NOT AVAILABLE
рН	NOT AVAILABLE
Vapour density	2.1 (Air = 1)
Specific gravity	0.79 (Approximately)
Solubility (water)	MISCIBLE
Vapour pressure	33 mm Hg @ 20°C (Isopropanol)
Upper explosion limit	12 % (Isopropanol)
Lower explosion limit	2 % (Isopropanol)
Partition coefficient	NOT AVAILABLE
Autoignition temperature	399°C (Isopropanol)
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

# **10. STABILITY AND REACTIVITY**

### 10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

### 10.2 Chemical stability

Stable under recommended conditions of storage.

### 10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

### 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

### 10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), metals, heat and ignition sources.

### 10.6 Hazardous decomposition products

May evolve carbon oxides and hydrocarbons when heated to decomposition.

# ChemAlert.

# **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

Acute toxicity

Information available for the product:

Based on available data, the classification criteria are not met.

### Information available for the ingredient(s):

Ingredient		Oral Toxicity (LD50)	Dermal Toxicity (LD50)	Inhalation Toxicity (LC50)
ISOPROPYL ALCOHOL		3600 mg/kg (mouse)	12,800 mg/kg (rabbit)	16000 ppm/8 hours
Skin Contact may result in irritation		n, redness, rash and derma	atitis.	
Eye	Irritating to the eyes. Contact	t may result in irritation, lac	rimation, pain and redness.	
Sensitization	Not classified as causing skin or respiratory sensitisation.			
Mutagenicity	Not classified as a mutagen.			
Carcinogenicity	Not classified as a carcinogen.			
Reproductive	Not classified as a reproductive toxin.			
STOT – single exposure	Over exposure may result in irritation of the nose and throat, coughing and headache. High level exposure may result in nausea, dizziness and drowsiness.			
STOT – repeated exposure	Not classified as causing organ damage from repeated exposure. There is currently insufficient evidence damage to the central nervous system (CNS), liver and kidney from repeated exposure.			
Aspiration	Not classified as causing aspiration.			

# **12. ECOLOGICAL INFORMATION**

### 12.1 Toxicity

No information provided.

### 12.2 Persistence and degradability

This product is readily biodegradable.

#### 12.3 Bioaccumulative potential

This product is not expected to bioaccumulate.

### 12.4 Mobility in soil

Relatively volatile and would therefore readily evaporate from dry soil and surfaces.

### 12.5 Results of PBT and vPvB assessment

No information provided.

### 12.6 Other adverse effects

No information provided.

### **13. DISPOSAL CONSIDERATIONS**

### 13.1 Waste treatment methods

Waste disposal For small amounts, absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information if disposing of large quantities (if required). Prevent contamination of drains and waterways as aquatic life may be threatened and environmental damage may result.

Legislation Dispose of in accordance with relevant local legislation.



### 14. TRANSPORT INFORMATION

### CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF ADR, IMDG AND/OR IATA



	LAND TRANSPORT (ADR / RID)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1219	1219	1219
14.2 Proper Shipping Name	ISOPROPANOL (ISOPROPYL ALCOHOL)	ISOPROPANOL (ISOPROPYL ALCOHOL)	ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3 Transport hazard class	3	3	3
14.4 Packing Group	Ш	II	II

14.5 Environmental hazards No information provided

14.6 Special precautions for user

EMS

F-E, S-D

# 15. REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Hazardous substance or mixture according to EC-directives 67/548/EEC or 1999/45/EC.

Classifications	F Xi Xn	Flammable Irritant Harmful
Risk phrases	R11 R36 R67	Highly flammable. Irritating to eyes. Vapours may cause drowsiness and dizziness.
Safety phrases	S2 S7 S16 S24/25 S26	Keep out of reach of children. Keep container tightly closed. Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
Inventory listing(s)	EUROPE:EINECS (European Inventory of Existing Chemical Substances) All components are listed on EINECS, or are exempt.	

### 15.2 Chemical safety assessment

No information provided.

### **16. OTHER INFORMATION**

Additional information

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

WORK PRACTICES - SOLVENTS: Organic solvents may present both a health and flammability hazard. It is recommended that engineering controls should be adopted to reduce exposure where practicable (for example, if using indoors, ensure explosion proof extraction ventilation is available). Flammable or combustible liquids with explosive limits have the potential for ignition from static discharge. Refer to AS 1020 (The control of undesirable static electricity) and AS 1940 (The storage and handling of flammable and combustible liquids) for control procedures.

# ChemAlert.

### PRODUCT NAME ENDUROSHIELD RAIN REPELLENT

EXPOSURE STANDARDS - TIME WEIGHTED AVERAGE (TWA) or WES (WORKPLACE EXPOSURE STANDARD) (NZ): Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: Strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

#### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

### HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations	ACGIH CAS # CNS DNEL EC No. EMS GHS IARC LC50 LD50 mg/m <sup>3</sup> OEL PBT pH PNEC ppm REACH STEL STOT-RE STOT-RE STOT-SE TLV TWA vPvB	American Conference of Governmental Industrial Hygienists Chemical Abstract Service number - used to uniquely identify chemical compounds Central Nervous System Derived No Effect Level EC No - European Community Number Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods) Globally Harmonized System International Agency for Research on Cancer Lethal Concentration, 50% / Median Lethal Concentration Lethal Dose, 50% / Median Lethal Dose Milligrams per Cubic Metre Occupational Exposure Limit Persistent, bioaccumulative, toxic relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline). Predicted No Effect Concentration Parts Per Million Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals Short-Term Exposure Limit Specific target organ toxicity (repeated exposure) Specific target organ toxicity (single exposure) Threshold Limit Value Time Weighted Average Very Persistent and Very Bioaccumulative		
Report status	This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.			
	While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.			
Prepared by	Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmt.com.au Prepared in accordance with: Annex II of the REACH Regulation (EC) 1907/2006: (CLP) Regulation			

# ChemAlert.

(EC) 1272/2008; and Regulation (EC) 453/2010 (Amendments to (EC) 1272/2008).

[ End of SDS ]

