SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name EC

Synonyms GLASS COATING

1.2 Uses and uses advised against

Uses GLASS COATING

EASY TO CLEAN GLASS COATING

UFI: V800-90NE-U00X-P1TA

1.3 Details of the supplier of the product

Supplier name EnduroShield Europe B.V.

Address Slimdijk 4 1631 DB Oudendijk - The

Telephone Netherlands+ 31 208081445

Email saleseurope@enduroshield.com

Website http://www.enduroshield.com/

1.4 Emergency telephone numbers

Emergency + 31 208 081 445

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFICATION ACCORDING TO REGULATION (EC) NO. 1272/2008 [CLP/GHS]

Physical Hazards

Flammable Liquids: Category 2

Health Hazards

Skin Corrosion/Irritation: Category 2

Serious Eye Damage / Eye Irritation: Category 2A

Specific Target Organ Toxicity (Single Exposure): Category 3 (Respiratory Irritation) Specific Target Organ Toxicity (Single Exposure): Category 3 (Narcotic Effects)

Environmental Hazards

Not classified as an Environmental Hazard

2.2 GHS Label elements

Signal word DANGER

Pictograms





Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.



PRODUCT NAME EC GLASS COATING

Prevention statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response statements

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P321 Specific treatment is advised - see first aid instructions.
P332 + P337 + P313 If skin or eye irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before re-use.
P370 + P378 In case of fire: Use appropriate media for extinction.

Storage statements

P403 + P233 + P235 Store in a well-ventilated place. Keep cool. Keep container tightly closed.

P405 Store locked up.

Disposal statements

P501 Dispose of contents/container in accordance with relevant regulations.

2.3 Other hazards

No information provided.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
ISOPROPYL ALCOHOL	67-63-0	200-661-7	85 to 95%
NON HAZARDOUS INGREDIENTS	Not Available	Not Available	Remainder

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to

stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion For advice, contact the UK National Poisons Information Service on 844 892 0111 or a doctor (at once). If

swallowed, do not induce vomiting.

First aid facilities Eye wash facilities and safety shower should be available.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to the eyes. Vapours may cause drowsiness and dizziness.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.



SDS Date: 15 Mar 2021 Version No: 1.4

Page 2 of 8

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide, foam or water fog. Prevent contamination of drains or waterways.

5.2 Special hazards arising from the substance or mixture

Highly flammable. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Vapour may form explosive mixtures with air. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, mobile phones, etc when handling. Earth containers when dispensing fluids.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Large storage areas should be bunded and have appropriate ventilation systems.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
Ingredient	Kelelelice		mg/m³	ppm	mg/m³
2-Propanol	OEL [Norway]	100	245		
Propan-2-ol	FIOSH [Germany]	200	500		
Propan-2-ol	WEL [UK]	400	999	500	1250

Biological limits

Ingredient	Determinant	Sampling Time	BEI
ISOPROPYL ALCOHOL	Acetone in urine	End of shift at end of workweek	40 mg/L

Reference: ACGIH Biological Exposure Indices



PRODUCT NAME EC GLASS COATING

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof

extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back.

Maintain vapour levels below the recommended exposure standard.

PPE

Eye / Face Wear splash-proof goggles. **Hands** Wear nitrile or neoprene gloves.

Body When using large quantities or where heavy contamination is likely, wear coveralls.

Respiratory Where an inhalation risk exists, wear a Type A (Organic vapour) respirator. If spraying, wear a Type A-Class

P1 (Organic gases/vapours and Particulate) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance CLEAR COLOURLESS TO PALE YELLOW LIQUID

Odour

Flammability

Flash point

Boiling point

Melting point

Evaporation rate

ALCOHOL LIKE ODOUR

HIGHLY FLAMMABLE

12°C (cc) (Isopropanol)

82.4°C (Isopropanol)

-90°C (Isopropanol)

NOT AVAILABLE

pH 1.1 to 1.5

Vapour density NOT AVAILABLE Specific gravity 0.79 (Approximately)

Solubility (water) MISCIBLE

Vapour pressure 33 mm Hg @ 20°C (Isopropanol)

Upper explosion limit 12 % (Isopropanol) Lower explosion limit 2 % (Isopropanol) Partition coefficient **NOT AVAILABLE** 399°C (Isopropanol) Autoignition temperature **Decomposition temperature NOT AVAILABLE NOT AVAILABLE Viscosity Explosive properties NOT AVAILABLE NOT AVAILABLE** Oxidising properties **Odour threshold** NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), metals, heat and ignition sources.

10.6 Hazardous decomposition products

May evolve carbon oxides and hydrocarbons when heated to decomposition.



SDS Date: 15 Mar 2021 Version No: 1.4

Page 4 of 8

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Based on available data, the classification criteria are not met. **Acute toxicity**

Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
ISOPROPYL ALCOHOL	> 2000 mg/kg (rat)	> 2000 mg/kg (rat)	> 20 mg/L (rat)
	(NICNAS)	(NICNAS)	(NICNAS)

Skin Irritating to the skin. Contact may result in irritation, redness, rash and dermatitis. Irritating to the eyes. Contact may result in irritation, lacrimation and redness. Eve

Not classified as causing skin or respiratory sensitisation. Sensitisation

Mutagenicity Not classified as a mutagen. Carcinogenicity Not classified as a carcinogen. Reproductive Not classified as a reproductive toxin.

Over exposure may result in irritation of the nose and throat, coughing and headache. High level exposure STOT - single

may result in nausea, dizziness and drowsiness. exposure

Not classified as causing organ damage from repeated exposure. There is currently insufficient evidence of STOT - repeated exposure damage to the central nervous system (CNS), liver and kidney from repeated exposure.

Aspiration Not classified as causing aspiration.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

This product is readily biodegradable.

12.3 Bioaccumulative potential

This product is not expected to bioaccumulate.

12.4 Mobility in soil

Relatively volatile and would therefore readily evaporate from dry soil and surfaces.

12.5 Results of PBT and vPvB assessment

No information provided.

12.6 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

For small amounts, absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Waste disposal

Contact the manufacturer/supplier for additional information if disposing of large quantities (if required). Prevent contamination of drains and waterways as aquatic life may be threatened and environmental

damage may result.

Legislation Dispose of in accordance with relevant local legislation.



14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF ADR, IMDG AND/OR IATA



	LAND TRANSPORT (ADR / RID)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1993	1993	1993
14.2 Proper Shipping Name	FLAMMABLE LIQUID, N.O.S. (Contains isopropyl alcohol)	FLAMMABLE LIQUID, N.O.S. (Contains isopropyl alcohol)	FLAMMABLE LIQUID, N.O.S. (Contains isopropyl alcohol)
14.3 Transport hazard class	3	3	3
14.4 Packing Group	II	II	II

14.5 Environmental hazards

No information provided.

14.6 Special precautions for user

EMS F-E, S-E

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Classifications	F Xi Xn	Flammable Irritant Harmful
Risk phrases	R11 R36/37/38 R67	Highly flammable. Irritating to eyes, respiratory system and skin. Vapours may cause drowsiness and dizziness.
Safety phrases	S2 S7 S16 S24/25 S26 S36/37/39 S45	Keep out of reach of children. Keep container tightly closed. Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice Wear suitable protective clothing, gloves and eye/face protection. In case of accident or if you feel unwell seek medical advice immediately (show the label where possible).

Inventory listings EUROPE:EINECS (European Inventory of Existing Chemical Substances)

All components are listed on EINECS, or are exempt.

15.2 Chemical safety assessment

No information provided.

16. OTHER INFORMATION

Additional information

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

ChemAlert.

WORK PRACTICES - SOLVENTS: Organic solvents may present both a health and flammability hazard. It is recommended that engineering controls should be adopted to reduce exposure where practicable (for example, if using indoors, ensure explosion proof extraction ventilation is available). Flammable or combustible liquids with explosive limits have the potential for ignition from static discharge. Refer to AS 1020 (The control of undesirable static electricity) and AS 1940 (The storage and handling of flammable and combustible liquids) for control procedures.

EXPOSURE STANDARDS - TIME WEIGHTED AVERAGE (TWA) or WES (WORKPLACE EXPOSURE STANDARD) (NZ): Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: Strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

-					
Δ	nn	rev	แล	tic	ne

ACGIH	American Conference of Governmental Industrial Hygienists
CAS#	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
DNEL	Derived No Effect Level
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous

Goods)
GHS Globally Harmonized System

IARC International Agency for Research on Cancer

LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
OEL Occupational Exposure Limit
PBT Persistent, bioaccumulative, toxic

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

PNEC Predicted No Effect Concentration

ppm Parts Per Million

REACH Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals

STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

TLV Threshold Limit Value TWA Time Weighted Average

vPvB Very Persistent and Very Bioaccumulative

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.



PRODUCT NAME EC GLASS COATING

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmtglobal.com

Prepared in accordance with: Annex II of the REACH Regulation (EC) 1907/2006; (CLP) Regulation (EC) 1272/2008; and Regulation (EC) 453/2010 (Amendments to (EC) 1272/2008).

[End of SDS]



SDS Date: 15 Mar 2021 Version No: 1.4

Page 8 of 8